


## HPSTAR 250-15

Racord rotativ 

Cadru rezistent cu  
diametru de Ø 32 mm 



 Roti pneumatice

Spalare cu presiune	HPSTAR 250-15
Presiune max.	250 bar
Debit	15 l/min. - 900 l/h
Turatie motor	3400 rpm
Tip pompa	In linie
Model pompa	Annovi Reverberi
Protectie temperatura	Termo valva
Motor	EX 40 DUL SH
Tip motor	OHC 4 timpi
Aspirare aer	Turbo
Putere max.	14 cp - 3600 rpm
Cilindri motor	404 cm <sup>3</sup>
Combustibil	Benzina
Capacitate rezervor	7.0 l
Autonomie	2h 30 min.
Pornire motor	la sfoara
Senzor lipsa ulei	Da
Greutate	68 kg
Dimensiuni L/l/h (mm)	700 x 700 x 1060

### Echipare standard

Lance 1.1 m cu presiune ajustabila  
Duza din ceramica ce asigura o viata ultra-indelungata  
Furtun de presiune, 10 m lungime  
Manometru presiune  
Valva eliberare presiune  
Kit aplicare detergent inclus  
Protectie termica motor  
Sasiu sudat mecanic cu tubulatura Ø30 mm  
Protectie metal vopsita cu vopsea epoxy  
Maner cadru detasabil pentru a o transporta mai usor  
Roti pneumatice rezistente

Distribuitor local