

Generator de curent 400V



Echipament
fabricat
in Franta

Tristar 8510

Powered by:



SUBARU

Robin Industrial Products

**Conceput pentru utilizare
intensa in santiere**



Echipare optionala:

- Varianta DE = demaraj electric
- Varianta N/S = pornire automata
- Regulator de tensiune electronica AVR
- Pornire la cheie
- Pornire automatizata
- Kit diferential 30 mA + priza impamantare
- Kit roti
- Kit intretinere (filtre + ulei)

Echipare standard:

- Racire cu aer (filtru inclus)
- Senzor lipsa ulei (ce opreste functionarea motorului)
- 2 prize 220V / 50Hz Ip44 10/16A Schuko
- Protectie prize cu disjuncteur termic
- Pornire manuala la sfoara
- Cadru ranforsat cu diam. 30 mm

Servicii incluse:



Seria Tristar	8510 EX	8510 MTXL27 EX	8510 MTXL27 EX DE N/S
Voltaj	400V	400V	400v
Frecventa	50 Hz	50 Hz	50 Hz
Putere maxima 400V	9 kVA	9 kVA	9 kVA
	7.2 kW	7.2 kW	7.2 kW
In regim continuu 400V	5 kW	5 kW	5 kW
Putere max. 230V	3.7 kW	3.7 kW	3.7 kW
Amperaj 400V	13 A	13 A	13 A
Amperaj 230V	16 A	16 A	16 A
Tip motor	Subaru EX40	Subaru EX40	Subaru Ex40
Putere motor	14 cp / 3600 rpm	14 cp / 3600 rpm	14 cp / 3600 rpm
Combustibil	Benzina	Benzina	Benzina
Capacitate rezervor	7 l	25 l	25 L
Autonomie	3 h	12 h 20 min.	12 h 20 min.
Zgomot (la 7m)	72 dB(A)	72 dB(A)	72 dB(A)
Putere sonora	97 Lwa	97 Lwa	97 Lwa
Greutate	83.5 kg	94 kg	100.5 KG
Dimensiuni Lxlxh (mm)	855x555x542	870x570x610	870x570x610
Dimensiuni Lxlxh (ambalaj)	880x575x555	890x590x630	890x590x630

Distribuitor local